

Milliken® Infrastructure Solutions

Pipe Wrap®

Polyurethane Impregnated Glass Fiber System



The **Pipe Wrap system** is a fast, easy to use, durable, and cost-effective temporary emergency pipe repair solution. This resin-impregnated glass fiber cloth adheres to PVC, fiberglass, concrete, and all metal pipes. The Pipe Wrap system is resistant to most harsh chemicals and thermally stable at elevated temperatures. The system repairs leaks up to 450 psi, reinforces pipes, and protects against corrosion, abrasion and impact. System requires piping to be de-pressurized during application.

Mechanical Properties

PROPERTIES	UNITS	METHOD	VALUES
Application Time			3-5 minutes
Thermal Stability			up to 400°F
Tensile Modulus	PSI	D638	659, 206
Tensile Elongation	%	D638	1.2 ± 0.7
Coefficient of Expansion	(°C-1)	D696	1.92 x 10 ⁻⁵ ± 0.17 x 10 ⁻⁵
Compression Modulus	PSI	D695	53,448.44 ± 4779.70
Compression Strength	PSI	D695	13,754.48 ± 539.15
Thermal Expansion		E831-6	84 (um/m/°F) 28.8 (um/m/°C)
Poisson's Ratio		D3039-00	.150

Physical Properties

Stocked Width	2", 4", 5" & 6"
Fabric Orientation	Bi-axial 0° And 90°
Cure Ply Thickness	0.019 in (19 Mils) (0.48mm)

General Properties

Cure Time	30 Minutes between 50°F & 80°F
Chemical Resistance	Hydrochloric Acid 10%, Ammonia Sulfuric Acid 35%, Mek, Diesel, Ethyl Alcohol Ethylene Glycol, Acetone, Gasoline, Toluene, Xylenes, Crude Oil
Application Conditions Above	45° F (7° C) up to 120° F (49° C)

Typical Uses

The system is widely used for temporary and semi-permanent leak repairs and surface protection. The system is used heavily in tough process piping applications, including:

- Petroleum refineries
- Chemical handling
- Mining

Benefits

- Emergency offline leak repair
- Drinking water safe
- Bonds to any pipe
- Quick to set and easy to use

Storage

2 year shelf life when stored @ 75 °F. Shelf Life may be extended when stored at lower temperatures, but above 40 °F.



Before using any Milliken Infrastructure Solutions, LLC product, the user must review the most recent version of the product's technical data sheet, material safety data sheet and other applicable documents, available at infrastructure.milliken.com or by calling 1-855-655-6750. Milliken Infrastructure Solutions, LLC is a subsidiary of Milliken & Company. The Milliken logo is registered by Milliken & Company and used under license by Milliken Infrastructure Solutions, LLC, all rights reserved. The Milliken Infrastructure and Pipe Wrap logos are trademarks of Milliken Infrastructure Solutions, LLC.

infrastructure.milliken.com
855-655-6750

MILLIKEN INFRASTRUCTURE
A *Milliken* COMPANY